sames kremlin

Liquid paint
application solutions



40F260

Airless Flowmax® Paint Pump

Product highlights

- Flowmax® Bellows technology for zero maintenance
- Designed for moisture-sensitive and abrasive materials
- Extended lifetime



BOND • PROTECT • BEAUTIFY

www.sames.com

40F260

Airless Flowmax® Paint Pump

This Flowmax® pump is recommended for anti-corrosion applications.

Adapted industrial markets


ACE*


Industrial


Transportation


Wood


Railways

Technical data table

Designation	Value	Unit
Maximum Air Pressure	6 (87)	**bar (psi)**
Pump displacement	260 (16)	**cc/cycle (in^3/cycle)**
Fluid Output at 20 cycles / mn	5,20 (1.37)	**l/min (gal/min)**
Fluid Output at 60 cycles / mn	15,60 (4)	**l/min (gal/min)**
Free Flow Rate	15,60 (4)	**l/min (gal/min)**
Number of cycles per liter of products	4	
Height	1120 (44.50)	**mm (in)**
Width/depth	300 (11.80)	**mm (in)**
Depth	510 (20)	**mm (in)**
Maximum Material Pressure	240 (3480)	**bar (psi)**
Pressure ratio	40/1	
Weight	110 (242)	**kg (lbs)**
Maximum Temperature	50 (122)	**°C (°F)**
Power Source	Pneumatic	
Sound Level	85	**dbA**
Certification	CE II 2G T5	
Motor Type	Mechanical reversing block	
Pump Type	Flowmax	
Air Inlet Fitting	F 3/4" BSPP	
Material Inlet Port	M 38 x 150	
Material Outlet Port	M 3/4" JIC	
Wetted Parts	Hard chrome stainless steel, Polyethylene, Tungsten carbide, Stainless steel 303	

Marking

Product	Type
40F260	CE 0080 CE II 2G T5

*: "AgricultureConstruction and Earthmoving"

Technologies



2 Ball | Flowmax® | Flowmax® feeding

Description

No dynamic sealing with leak-free technology.

Performances

• High output to feed several guns in circulation
• High suction power for materials up to 4,000 cps
• Turbo air motor also available for continuous 24/7 use

Productivity

• Flowmax® Bellows technology provides total sealing (dust free) - no lubricant cup
• Ideal for moisture-sensitive catalyst and UV products

Sustainability

• Triple chrome piston and cylinder, stainless steel ball & carbide seat for long-term use
• Sleek design with fewer parts - inversion system provides fast changeover for constant material delivery
• Bellows lifetime 10,000,000 cycles - up to 8 years

Accessories

Designation	Part number
Stainless steel drain rod Ø16 elbowed F18 x 125	049596000
Suction rod Ø25 plunging tube length 570 mm	049597100
Pump bracket	051341206
SST NIPPLE 3/4 NPS	055581401
Fluid filter 3/4 mesh 12	155581400

Spare parts

Designation	Part number
GT SEAL KIT FOR FLUID SECTION F260	144020690
PU SEAL KIT FOR FLUID SECTION F260	144020691
PU REPAIR KIT FOR FLUID SECTION F260	144020692
GT REPAIR KIT FOR FLUID SECTION F260	144020695
Air Motor seal package	146280991
Air Motor Servicing kit	146280996
POLYURETHANE ROD SEAL (RED) FOR C240 AND F240	909060304
GT SEAL FOR HYDRAULIC C240, C260, F240, F260, F60	909150228

Equipment

Designation	Part number
40F260 GT WALL-MOUNTED PUMP	151871500
40F260 GT WALL-MOUNTED PUMP W/ FILTER AND ROD	151871600
AIRLESS PUMP 40F260 FLOWMAX PU W/M WITH FILTER AND SUCTION	151871660
40F260 TROLLEY-MOUNTED PUMP + FILTER	151871700
40F260 GT WALL-MOUNTED PUMP W/ FILTER	151871800

Additional information

- User manual
- Spare parts
- Accessories
- Documents
- Videos

Sames
13 chemin de Malacher
CS 70086 - 38243 MEYLAN Cedex - FRANCE
Phone: +33 (0)4 76 41 60 60
www.sames.com

Sames reserves the right to modify its equipment or specifications without further notice.
Document, products and pictures shown are not contractual.

11/2025